

ScalewatcherTM Industrial IIME



IIME

Markets:

The Industrial 5-6 range is to be used for heavy Industry i.e. paper factories, steel-, oil/offshore-, plastic-, chemical-, and sewer Industry and for protecting cooling towers, boilers, heat exchangers, chillers, process water lines etc. The range is used for the larger pipe sizes.

| Model | Diameter |
|--------|----------|
| HIME24 | 24" |
| HIME40 | 40" |

Technical specifications

| | |
|-----------------------------|---|
| Supply Voltage | 115 V \pm 10 %, 230 V \pm 20 %, adjusts automatically |
| Current Consumption | < 2 A |
| Overload protection | External replaceable fuse |
| Coil cable | Three core, 2.5 mm ² |
| Maximum Coil Temperature | 256 F |
| Capable of driving | 2 coils in series |
| Remote Alarm Output | Isolated alternating switch, relay operated |
| Output reading | Display reading relative output field strength |
| For pipe sizes up to | 40" |
| External visible indicators | Optional Warning Beacon |
| Protection rate | NEMA 4 |
| Weight packed | 25 lbs |
| Dimension unpacked | 14.5x15x8.5 |
| Maximum ambient temperature | 140 F |
| Minimum ambient temperature | -10 F |

Distributed by:

AD Process Supply

adprocesssupply.com

info@adprocesssupply.com

T: [416] 435-8207 F: [905] 342-2485

975A Elgin Street West - Unit 350, Cobourg, ON, K9A 5J3 Canada